

UltraCam-Xp w/a Technical Specifications

Image Product Specification

Image format	Analogous to an aerial film image at a format of 23 cm x 15 cm, scanned at 13 µm
Image data formats	JPEG; TIFF with options for 8 and 16 bits, standard tiff format
Image storage format in level 2	Full resolution panchromatic, separate color channels at color resolution
Color at level 3	Full resolution R, G, B, Near-IR channels, planar or pixel-interleaved

Digital Camera Technical Data (Sensor Unit S-Xp w/a)

Panchromatic image size	17,310 * 11,310 pixels
Panchromatic physical pixel size	6 µm
Input data quantity per image	624 Mega Bytes
Physical format of the focal plane	103.9 mm * 68.4 mm
Lens system	Linos Vexcel Apo-Sironar digital HR
Panchromatic lens focal distance	70 mm
Lens aperture	f = 1/5.6
Angle-of-view from vertical, cross track (along track)	73° (52°)
Color (multi-spectral capability)	4 channels -- RGB & NIR
Color image size	5,770 * 3,770 pixels
Color physical pixel size	6 µm
Lens system	Linos Vexcel Apo-Sironar digital HR
Color lens system focal distance	23 mm
Color lens aperture	f = 1/4.0
Color field of view from vertical, cross track (along track)	73° (52°)
Shutter system	Prontor magnetic 0 – Vexcel
Shutter speed options	1/500 to 1/32
Forward-motion compensation (FMC)	TDI controlled
Maximum FMC-capability	50 pixels
Pixel size on the ground (GSD) at flying height of 1000 m (at 500m)	8.6 cm (4.3 cm)
Frame rate per second (minimum inter-image interval)	1 frame per 2 seconds
Analog-to-digital conversion at	14 bits
Radiometric resolution in each color channel	>12 bit
Physical dimensions of the camera unit	45 cm x 45 cm x 60 cm
Weight	~ 55 kg
Power consumption at full performance	150 W

In Flight Data Storage D-Xp and Data Processing C-Xp

In-flight storage capacity	Unlimited with use of multiple data units D-Xp; per D-Xp unit ~4.2 TB
In-flight capacity to collect uncompressed frames	Unlimited with multiple D-Xp units; per D-Xp unit ~ 6,600 images
Method of exchanging D-Xp units in-flight	In less than 3 minutes
Configuration of Storage D-Xp and Computing C-Xp	C-Xp with 14 Pentium-M CPUs; each D-Xp with 14 disks
Redundancy	Storing mirror images of the data on two DXp units
Data transfer into office environment	Removable D-Xp data units; docking station (optionally mobile)
Physical dimensions	Width 50 cm x Depth 36 cm x Height 65 cm
Weight of C-Xp + 2 D-Xp	< 92 kg
Weight of C-Xp	~ 65 kg
Weight of single D-Xp	~ 16 kg
Power consumption at full performance	700 W

Operational Specification

Data collection period at 70% & 20 % overlap, at 20 cm GSD (film scale 1:10,000), 140knts	11 hours per single D-Xp unit
Post-processing of collected raw images	OPC Software, Mobile Server, Office PC Network, Laptop, C-Xp
Data transfer from aircraft to office	Shipping of D-Xp, or transfer to high capacity storage medium via Mobile Server
Mounting of the camera	Using adapter ring for all current film camera mounts (PAV-30, PAV-80, Z/I T-AS, GSM3000)
Flight planning support	Compatible with commercial systems (CCNS-4, Trackair, Vega,)
Exterior orientation support	Compatible with DGPS/IMU systems (IGI's Aero-Control, Applanix POS-AV)
Photogrammetric Production	TIFF-output compatible with Customer's photogrammetric production software
Image geometric accuracy	Better ±2 µm



For more Information, contact:

Vexcel Imaging GmbH | a Microsoft company
 Anzengrubergergasse 8
 A-8010 Graz, Austria
mpsinfo@microsoft.com | www.ultracamx.com